

## 0.18μm Generic II Logic Process

### FSA0A\_C 1.8V Crystal Oscillator I/O Cells

#### Key Features

- UMC's 0.18μm 1.8V/3.3V Generic II Logic Process
- High frequency oscillator pad range : 1MHz ~ 66MHz
- Low frequency oscillator pad range : 32KHz ~ 1MHz
- Programmable output driving capability
- Oscillation mode / power down (stop) mode / tri-state mode / parallel model
- Internal feedback resistance
- Built-in Antenna diodes for all pins
- ESD Robustness and Latch-up immunity proven by Silicon

#### General Description

This library is tailored for UMC's 0.18μm 1.8V/3.3V Generic II Logic Process. All I/O cells have been designed as programmable crystal oscillator I/O cells. Two layout structures, both optimized for pad limited and core limited designs, are available to support each programmable feature or function.

#### Quick Reference

Characteristic		Description
<b>Physical</b>	Process	UMC 0.18μm 1.8V/3.3V 1P6M Generic II Logic Process
	Cell Width * Cell Height	68.2μm * 235.6μm (Staggered) 125.24μm * 140.12μm (In-line)
	Cell Layout Metal	M1, M2, M3
	Power Ring Metal	M3 and above
	Layout Resolution	0.01μm
<b>Electrical</b>	Recommended Operating Conditions	Power Supply Voltage Core: 1.62V ~ 1.98V I/O: 1.62V ~ 1.98V
		Junction Temperature: -40°C ~ 125°C
	Frequency	High frequency oscillator pad: 1M ~ 66M Low frequency oscillator pad: 32K ~ 1M
	Input Threshold	LVTTL

#### HEADQUARTERS

Hsinchu, Taiwan,  
 Tel: 886-3-578-7888  
 Fax: 886-3-578-7889  
 sales@faraday-tech.com

#### USA OFFICE

Sunnyvale, USA  
 Tel: 1-408-522-8888  
 Fax: 1-408-522-8889  
 sales@faraday-usa.com

#### EUROPE OFFICE

Hoofddorp, Netherlands  
 Tel: 31-2356-20496  
 Fax: 31-2356-36297  
 eusales@faraday-tech.com

#### JAPAN OFFICE

Tokyo, Japan  
 Tel: 81-3-5214-0070  
 Fax: 81-3-5214-0076  
 sales@faraday.co.jp

#### CHINA OFFICE

Shanghai, P. R. China  
 Tel: 86-21-6406-7523  
 Fax: 86-21-6406-5327  
 sales@faraday.com.cn