

0.18 μ m Logic 3.3V Generic I/Os

FSA0A_C 3.3V Generic I/O Cells

Key Features

- UMC's 0.18 μ m 1.8V/3.3V Generic II Logic Process
- 3.3V input, 3.3V output drive
- Output buffer with programmable drive strength from 2mA to 16mA with 2mA step
- Input buffer with programmable pull up resistance, pull down resistance, keeper, and Schmitt trigger
- Built-in Antenna diodes for all pins
- ESD Robustness and Latch-up immunity proven by Silicon

General Description

This library is tailored for UMC's 0.18 μ m 1.8V/3.3V Generic II Logic Process. All I/Os are equipped with a rich selection of programmable features capable of adapting to a wide variety of application environments. Two layout structures, both optimized for pad limited and core limited designs, are available to support each programmable feature or function.

Quick Reference

Characteristic		Description
Physical	Process	UMC 0.18 μ m 1.8V/3.3V 1P6M Generic II Logic Process
	Cell Width * Cell Height	34.1 μ m * 235.6 μ m (Staggered) 62.62 μ m * 140.12 μ m (In-line)
	Cell Layout Metal	M1, M2, M3
	Power Ring Metal	M3 and above
	Layout resolution	0.01 μ m
Electrical	Recommended Operating Conditions	Power Supply Voltage Core: 1.62V ~ 1.98V I/O: 2.97V ~ 3.63V
		Junction Temperature: -40°C ~ 125°C
	Driving Strength	2mA~16mA by 2mA step
	Input Threshold	LVTTL
	Pull Up/Down resistance	75K Ohm

HEADQUARTERS

Hsinchu, Taiwan,
 Tel: 886-3-578-7888
 Fax: 886-3-578-7889
 sales@faraday-tech.com

USA OFFICE

Sunnyvale, USA
 Tel: 1-408-522-8888
 Fax: 1-408-522-8889
 sales@faraday-usa.com

EUROPE OFFICE

Hoofddorp, Netherlands
 Tel: 31-2356-20496
 Fax: 31-2356-36297
 eusales@faraday-tech.com

JAPAN OFFICE

Tokyo, Japan
 Tel: 81-3-5214-0070
 Fax: 81-3-5214-0076
 sales@faraday.co.jp

CHINA OFFICE

Shanghai, P. R. China
 Tel: 86-21-6406-7523
 Fax: 86-21-6406-5327
 sales@faraday.com.cn