

0.18 μ m Generic II Logic Process

FSA0A_C LVPECL I/O Cells

Key Features

- UMC's 0.18 μ m 1.8V/3.3V Generic II Logic Process
- 3.3V PECL I/O cells
- Options for 25 ohms and 50 ohms output buffers
- 300MHz for differential type drivers and receivers
- 250MHz for single-ended type driver and receivers
- Support power down mode
- Built-in Antenna diodes for all pins
- ESD Robustness and Latch-up immunity proven by Silicon

General Description

This library is tailored for UMC's 0.18 μ m 1.8V/3.3V Generic II Logic Process. For high-speed chip-to-chip communications with specified DC drive characteristics, these differential type receivers and drivers provide data transfer rates up to 300Mbps. Single-ended type buffers are provided for lower power consumption. For improved noise performance (due to common mode noise rejection) these cells provide differential type buffers. Staggered and In-line structures are provided for all PECL I/O cells to fit pad limit or core limit designs.

Quick Reference

Characteristic		Description
Physical	Process	UMC 0.18 μ m 1.8V/3.3V 1P6M Generic II Logic Process
	Cell Width * Cell Height	34.1 μ m * 235.6 μ m (Staggered single ended input buffer)
		40.92 μ m * 235.6 μ m (Staggered single ended output buffer)
		62.62 μ m * 140.12 μ m (In-line single ended input buffer)
		69.44 μ m * 140.12 μ m (In-line single ended output buffer)
	Cell Layout Metal	M1, M2, M3
Power Ring Metal	M3 and above	
Layout Resolution	0.01 μ m	
Electrical	Recommended Operating Conditions	Power Supply Voltage Core: 1.62V ~ 1.98V I/O: 2.97V ~ 3.63V
		Junction Temperature: -40°C ~ 125°C
	Output Impedance	25 Ohms and 50 Ohms

HEADQUARTERS

Hsinchu, Taiwan,
 Tel: 886-3-578-7888
 Fax: 886-3-578-7889
 sales@faraday-tech.com

USA OFFICE

Sunnyvale, USA
 Tel: 1-408-522-8888
 Fax: 1-408-522-8889
 sales@faraday-usa.com

EUROPE OFFICE

Hoofddorp, Netherlands
 Tel: 31-2356-20496
 Fax: 31-2356-36297
 eusales@faraday-tech.com

JAPAN OFFICE

Tokyo, Japan
 Tel: 81-3-5214-0070
 Fax: 81-3-5214-0076
 sales@faraday.co.jp

CHINA OFFICE

Shanghai, P. R. China
 Tel: 86-21-6406-7523
 Fax: 86-21-6406-5327
 sales@faraday.com.cn