

## 0.25μm Logic Process

### FS90A\_C 2.5V Crystal Oscillator I/O Cells

#### Key Features

- UMC's 0.25μm 2.5V/3.3V logic process
- High frequency oscillator pad range : 1MHz ~ 66MHz
- Low frequency oscillator pad range : 32KHz ~ 1MHz
- Programmable output driving capability
- Oscillation mode / power down (stop) mode / tri-state mode / parallel model
- Internal feedback resistance
- Built-in antenna diodes for all input pins from core
- Dedicated power and ground for noise immunity
- ESD robustness and latch-up immunity proven by silicon

#### General Description

This library is tailored for UMC's 0.25μm 2.5V/3.3V Logic Process. All I/O cells have been designed as programmable crystal oscillator I/O cells. Two layout structures, both optimized for pad limited and core limited designs, are available to support each programmable feature or function.

#### Quick Reference

Characteristic		Description
<b>Physical</b>	Process	UMC 0.25μm 2.5V/3.3V 1P5M Logic Process
	Cell Width * Cell Height	182.32μm * 237.36μm (Staggered) 251.12μm * 141.9μm (In-line)
	Cell Layout Metal	M1, M2, M3
	Power Ring Metal	M3 and above
	Layout Resolution	0.01μm
<b>Electrical</b>	Recommended Operating Conditions	Power supply voltage Core: 2.25V ~ 2.75V I/O: 2.25V ~ 2.75V
		Junction temperature: -40°C ~ 125°C
	Frequency	High frequency oscillator pad: 1M ~ 66M Low frequency oscillator pad: 32K ~ 1M

#### HEADQUARTERS

Hsinchu, Taiwan,  
 Tel: 886-3-578-7888  
 Fax: 886-3-578-7889  
 twsales@faraday-tech.com

#### USA OFFICE

Sunnyvale, USA  
 Tel: 1-408-522-8888  
 Fax: 1-408-522-8889  
 ussales@faraday-tech.com

#### EUROPE OFFICE

Hoofddorp, Netherlands  
 Tel: 31-2356-20496  
 Fax: 31-2356-36297  
 eusales@faraday-tech.com

#### JAPAN OFFICE

Tokyo, Japan  
 Tel: 81-3-5214-0070  
 Fax: 81-3-5214-0076  
 jpsales@faraday-tech.com

#### CHINA OFFICE

Shanghai, P. R. China  
 Tel: 86-21-6406-7523  
 Fax: 86-21-6406-5327  
 cnsales@faraday-tech.com